

UNIVERSAL PRIMER

TIE-COAT FOR UNI-TECHNOLOGY SYSTEM AF

N08002

PRODUCT DESCRIPTION Rust preventive binder coat for Uni-Technology System
& INTENDED USES

FEATURES

- Good compatibility with JOTAMASTIC UNIVERSAL or EPOMARINE SUPER EX21AC
- Good compatibility with self-polishing anti-foulings
- Excellent resistance to sea water and cathodic protection
- Quick Drying

COLOUR(S) Silver

APPLICATION METHOD

Airless spray	: Recommended
Nozzle tip	: 0.019"
Fluid pressure	: 100~150kg/cm ²
Thinning	: 0~8% by volume
Conventional spray, brush or roller	

THINNER Thinner No.12

MIXING RATIO Ready to use

POT LIFE	【Temperature】	5 °C	10 °C	20 °C	30 °C
		--	--	--	--

TYPICAL FILM THICKNESS	【Wet】	197 μm
	【Dry】	70 μm

SOLID VOLUME RATIO 36 %

SPREADING RATE

【Theoretical】	5.1 m ² /litre
【Practical】	Varies depending on surface conditions, environment, application, etc.

DRYING TIME	【Temperature】	5 °C	10 °C	20 °C	30 °C
	【Set to touch】	30 min.	25 min.	20 min.	10 min.
	【Dry Hard】	5 hrs.	4 hrs.	3 hrs.	2 hrs.
	【Before Flooding】	--	--	--	--

OVERCOATING INTERVAL	【Minimum】	6 hrs.	5 hrs.	4 hrs.	3 hrs.
	【Maximum】	--	--	--	--

SHELF LIFE 12 months