

## PLATINITE R

ALUMINIUM PAINT

N11050

**PRODUCT DESCRIPTION & INTENDED USES** Aluminium paint for machinery, pipes, rails and interior surface in funnel that can withstand continuous exposure up to 100°C and up to 150°C for a short while.

**FEATURES**

- Good heat resistance
- Good weathering resistance

**COLOUR(S)** Silver

**APPLICATION METHOD**

Airless spray	: Recommended
Nozzle tip	: 0.019~0.021"
Fluid pressure	: 100~150kg/cm <sup>2</sup>
Thinning	: 0~5% by volume
Conventional spray, brush or roller	

**THINNER** Thinner No. 2

**MIXING RATIO** Ready to use

**POT LIFE**

<b>【Temperature】</b>	5 °C	10 °C	20 °C	30 °C
	--	--	--	--

*Silver*

**TYPICAL FILM THICKNESS**

<b>【Wet】</b>	42 μ m
<b>【Dry】</b>	20 μ m

**SOLID VOLUME RATIO** 48 %

**SPREADING RATE**

<b>【Theoretical】</b>	24.0 m <sup>2</sup> /litre
<b>【Practical】</b>	Varies depending on surface conditions, environment, application, etc.

**DRYING TIME**

<b>【Temperature】</b>	5 °C	10 °C	20 °C	30 °C
<b>【Set to touch】</b>	2 hrs.	2 hrs.	1 hr.	1 hr.
<b>【Dry Hard】</b>	6 hrs.	5 hrs.	3 hrs.	2 hrs.
<b>【Before Flooding】</b>	--	--	--	--

**OVERCOATING INTERVAL**

<b>【Minimum】</b>	24 hrs.	20 hrs.	16 hrs.	12 hrs.
<b>【Maximum】</b>	--	--	--	--

**SHELF LIFE** 12 months